

SETTING NEW



HYPER GRINDER

RTK 280

MADE IN ITALY



PROFESSIONAL SANDER WITH SINGLE DISC AND VARIABLE SPEED IDEAL FOR GRINDING FLUSH AGAINST WALLS.

RTK 280 is a single disc sander, very compact with high performance, easy to transport, and reaches narrow and impractical areas. Thanks to the articulated head and the opening tool cart with guided wheels on both sides, the RTK 280 can also be transformed into an effective edge sander in just a few seconds.

MAIN CHARACTERISTICS:

- Tool casing height only 100 mm! Smooth under shelves etc.
- Perfectly balanced during sanding with vibration levels much lower than other market appliances.
- Swivel head on three angles: left, center and right. Operation can be performed in seconds and without tools.
- Tool holders mounted on a levitating joint that follows the floor at all times.
- Quick, safe and fast tool change without the use of a key or hammer.
- Height adjustable wheels.
- Detachable chassis for easy transport.

Model	Motor	Amp	Volt	Hertz	Tool Speed	Working Area	Tool Size	Water Tank	Size LxAxP cm	Weight
RTK 280	2,6 kW	14	1x230	50	1400 rpm	280mm	1x280mm	8 It optional	90x75x39	55 Kg
RTK 280 VS	3 kW	12,5	1x230	50/60	840 - 1680 rpm	280mm	1x280mm	8 It optional	90x75x39	55 Kg

HYPER GRINDER

TECHNICAL DATA

Compact and performing single disc grinder, operates flush against walls.





Swivel head on three angles: left, center and right. Operations can be performed in seconds and without extra tools.



Quick tool change, speedy and safe. Tools are available for any need. RTK280 allows effective removal of glues and resins.



The girating head together with the guided wheels allows the edge to be accessed.



Foldable handle reduces space during transport. Thanks to the compact design RTK280 easily enters any vehicle.

RTK 200



Bush-hammering disc.



On-board polishing with HCR and GIAGUAR FLEX resinoid disks.



The guided wheel allows the optimal working position and facilitates the smoothing of the wall.







The quick release covers allows a speedy conversion to wall grinding on two sides.



Reverse rotation option button for the disk.



Spirit levels for perfect balance of work surface.



Additional socket on board.







HG HYPER GRINDER S.R.L Via Chieti, 6 | 65121 Pescara (PE) | ITALY P.lva 02223280682 | hypergrinder@pec.it | Tel +39 085 9117448 www.hypergrinder.com |info@hypergrinder.com —Your Official Dealer: —

